

# GRAFFITISLATE

ORIGIN: Brasil

Black shaded slate with grey tones, typical slate texture and well-developed veining.



MEASURES Standard: 60x30cm, 60x40cm. Thickness: 1 to 3cm.  
Can be produced in any size up to 200x100cm.

APPEARANCE	Main color	Secondary colour	Tone	Tone variation	Finish*
	BLUE	BLACK	DARK	LOW	-

\* Finish: Natural/natural, natural/calibrated, calibrated/brushed, calibrated/honed, bullnose.

FEATURES	Texture	Absorption	Oxidation	Strength	Cleaning
	SLATE TEXTURE	LOW	NO	GOOD	EASY

RECOMMENDED APPLICATIONS	Interior wall	Exterior wall	Interior flooring	Exterior flooring	Garden	Swimming Pool	Road surface	Pavement
	YES	YES	YES	YES	YES	NO	YES	YES

TECHNICAL INFORMATION	Specific weight (kg/m <sup>3</sup> )	2.720kg/m <sup>3</sup>
Water absorption (%)	0.58±0.0%	
Reaction to fire	A1	
Bending strenght (MPa)	Dry/Med.Value 45.59±9.83MPa Vie: 26.32MPa	
Frost resistance (MPa)	Resistant after 48 cycles: Med.Value 27.33±11.88MPa Vie: 7.94MPa	
Abrasive resistance (mm)	27.6mm.	
Slip resistance (mm)	SRV Values (natural finish): dry: 75 / wet: 59	

Test results and technical information available in: [CUPA-STONE.COM](http://CUPA-STONE.COM)

# GRAFFITISLATE

Actual size.

